



➔ L-Bracket

Dimensions(LxWxD) : 250mm x 48mm x 30mm

Finishing : Anodized finish

Open Mode : 90 Door

Material : Zinc

Bracket Type : L Shaped

Suitable for : In/Out-swing Door

Net Weight : 0.242kg

Features:

- ▶ Used for EM-LOCK SUPPORT on WALL or fall Ceiling
- ▶ These brackets are very reliable or strong product
- ▶ Consistent
- ▶ Easy to manage
- ▶ Resilient



➔ ZL-Bracket

Dimension : L bracket – 250L x 48W x 30H mm
: Z bracket – 185L x 50W x 50H mm

Finishing : Anodized finish

Open Mode : 90 Door

Bracket Type : L Shaped

Suitable for : In/Out-swing Door

Net Weight : 0.378kg

Features:

- ▶ Used for EM-LOCK SUPPORT on WALL or fall Ceiling
- ▶ These brackets are very reliable or strong product
- ▶ Consistent
- ▶ Easy to manage
- ▶ Resilient



➔ Bolt Lock Bracket

Glass thickness : 9-15mm

Dimensions(LxWxD): 90mm x 51mm x 25.5mm

Material : Aluminium

Finishing : Anodized finish

Features:

- ▶ Suitable for glass thickness: 9-15mm
- ▶ Construction: stainless steel plate
- ▶ Anodized finish



➔ Strike Lock

Voltage Input : 12V DC

Current : 12V / 850 mA

Operating Temperature : 0° C - 55° C

Operating Humidity : 0% - 95%

Dimensions Magnet (LxWxT) : 500 x 42 x 25 mm

Armature (LxWxT) : 80 x 38 x 11 mm

Anti-Rust Surface Treatment : Zinc Plating

Suitable for : Wooden door, Metal door

Safety : Fail Secure (NO)

Features:

- ▶ Special, wide-mounted, concealed installation
- ▶ Power-off to lock
- ▶ Counter locking function with extended panel
- ▶ 90 degrees swinging door, suitable for metal door
- ▶ Aluminum, Stainless Steel Bolt
- ▶ Fail Secure (NO)