



ET1022

➔ ET1022 : Heavy Duty Tripod Turnstile

Passage Width : $\leq 550\text{mm}$

Throughput rate : 35p/m

Power Supply : 100 ~ 240V

Operational Voltage : 24V

Max Power Consumption : 30 W

Frequency : 50~60hz

Protection Level : ≥ 44

Working Temperature : $-25 \sim +70^{\circ}\text{C}$

Electro - magnetic Drive : DC

Dimension Excluding Bar : 480x280x980 mm

Net Weight Including Bar : 44kg

Features:

Controller

- ▶ Semi-Auto mode
- ▶ Full-Auto mode
- ▶ Pure Mechanical mode
- ▶ Single or Bi-directional function in mechanical and electrical versions

- ▶ Automatic reset of barrier arms after each passage

- ▶ Adjustable time out delay

Operating Mode

- ▶ Single passage in the set direction
- ▶ Bi-directional passage
- ▶ Free passage in the set direction
- ▶ Always free or locked

Secondary Controller :

- ▶ Users : 30,000 (RFID)
- ▶ Fingerprint : 3000
- ▶ Transaction storage : 1,00,000
- ▶ Integrated Controller : inbio-260
- ▶ Relay : 12 V relay for lock
- ▶ Support Fire Alarm : Yes

Reader :

- ▶ RFID : Yes | Fingerprint : Yes

Protocol : RS485 / Mifare/Proxy (Optional) : Yes