



➔ Swing Barrier

Passage width (Max) : 450mm
Throughput rate : 35 P/M
Power Supply : 100V ~ 240V AC
Operational Voltage : 24V DC
Max Power Consumption : 30W
Frequency : 50Hz ~ 60Hz
Protection Level (IP) : ≥ 54
Working Temperature : $-25^{\circ} \sim +70^{\circ}$
Electro-magnetic Drive : DC
Dimension excluding bars :
480 X 280 X 1050 mm
New weight (Including Bars) : 40kg

Feature :

- ▶ Use IC cards, ID cards, bar code or magnetic cards as automatic identification system.
- ▶ Display has been in use for statistics and numbers
- ▶ With voice and strobe light alerts
- ▶ A combination of infrared sensors and police anti-illegal entry into pedestrian access.
- ▶ Double anti-clipping function, photocell anti-clipping and mechanical anti-clipping
- ▶ The barrier can be set to delay closing in 1 ~ 60s after a valid card reading
- ▶ Single passage in the set direction
- ▶ Bi-directional single passage
- ▶ Free passage in the direction
- ▶ Always free or locked

Swing Barrier



- Use IC cards, ID cards, bar code or magnetic cards as automatic identification system
- Display has been in use for statistics and numbers
- With voice and strobe light alerts
- A combination of infrared sensors and police anti-illegal entry into pedestrian access
- Double anti-clipping function, photocell anti-clipping & mechanical anti-clipping
- The barrier can be set to delay closing in 1 ~ 60s after a valid card reading
- Single passage in the set direction
- Bi-directional single passage
- Free passage in the direction
- Always free or locked